

IMPLEMENT MASSEY FERGUSON ACCESSORIES







Maintain the perfect cut and versatile performance in the field.

Don't compromise your Massey Ferguson implement's performance. Ensure you only use Genuine Massey Ferguson replacement parts and accessory kits.

If the grass kits range highlighted does not include the part or application you are looking for, don't hesitate to contact your local dealer for more information.









Drum mowers

M Accessories





Cat. II triangular coupling frame

FEL161748

M 254 FP M 294 FP-V M 304 FP-V M 334 FP-V



Swath deflector system

 Consisting of 2 rotating swath discs on the right + 2 on the left



FEL42992409

M 294 M 304 TL



Additional swath discs

Swath width ca.

- 0,65 1,00 m
- 0,65 1,20 m
- 0,85 1,40 m

FEL42807609

M 294 FP-V M 304 FP-V M 334 FP-V



Telescopic upper linkage CAT. II, lockable

• Adjustable distance: 500 - 700 mm / telescopic distance: 80 mm

FEL141869

M 254 FP M 294 FP-V M 304 FP-V M 334 FP-V



Disc mowers

DM Accessories



Dividing disc

- For fitting on the feeder drums
- Better dividing of the forage on the outside

FEL42989609

DM cutterbar (compact angular gear)



Gearbox 540 RPM

FEL429920

DM 316 TL-V DM 316 TL-V-KC DM 316 TL-V-RC



Supports for parking with mower in vertical position

FEL429908

DM 316 TL-V/KC/RC DM 367 TL-V/ KC/RC





Spreader device for TLX/TL-V



FEL429900	DM	316	TL-V-KC
-----------	----	-----	---------

FEL429901 DM 367 TL-V-KC

FEL429903 DM 316 TL-V-RC

FEL429904 DM 367 TL-V-RC



Hydraulically folding end cover

FEL429910 DM 316 TL-V

DM 316 TL-V-KC DM 316 TL-V-RC

FEL492909 DM 367 TL-V

DM 367 TL-V-KC DM 367 TL-V-RC



Disc mowers

DM Accessories



Hydraulic transport locking system TLX/TL-V; additional SAV required

FEL429914

DM 316 TL-V/KC/RC DM 367 TL-V/KC/RC



Lighting set TLX/TL-V

FEL429897

DM 316 TL-V/KC/RC DM 367 TL-V/KC/RC



Additional skid

- For larger cutting heights: at least 2 pieces required for each cutter bar
- As wear protection for stony or sandy conditions (number of mower discs = number of additional anti-wear skids)

FEL429918

DM 316 TL-V/KC/RC DM 367 TL-V/KC/RC





Electrical lightning and warning panels

FEL17259009

DM 306 FP DM 306 FP-SL DM 306 FP-KC DM 306 FP-RC



Electrical lightning and warning panels

FEL17259109

DM 306 FP-K



1 welded-on skid

At least 3 necessary for each mower.

FEL425927

DM InLine DM ISL



Disc mowers

DM Accessories



Protective cover

• for use without conditioner

FEL42989305

DM 306 FP-SL DM 306 FP-KC DM 306 FP-RC DM 306 FZ-KC DM 306 FZ-RC DM 306 TR-KC DM 306 TR-RC



Set of suppression hoops



FEL42989509

DM 306 FP-K DM 306 FP/SL/KC/RC DM 306 FZ/KC/RC DM 313 TR-KC/RC





Cat. II triangular coupling frame

FEL161748

DM 254 FP
DM 254 FP-S
DM 306 FP-K
DM 306 FP-Old
DM 306 FP-SL old
DM 306 FP-RC old
DM 306 FP-RC old
DM 306 FP-RC old
DM 306 FP-SL new
DM 306 FP-KC new
DM 306 FP-RC new
DM 306 FZ-RC
DM 306 FZ-RC



Swath disc left


FEL426238

DM 204 DM 255 DM 255-P DM 306-P



1 additional skid

- For larger cutting heights: at least
 2 pieces (or 3 for working width larger 4,00 metre)
 required for each cutter bar
- As wear protection for stony or sandy conditions (number of mower discs = number of additional anti-wear skids)



FEL42630609

DM cutterbar (compact angular gear)



Disc mowers

DM Accessories



Spreader device

· Spreading the forage across the whole width for faster drying

FEL42724109

LMC 170 D

FEL42989409

DM 306 TR-KC



Quick-change set for blades

FEL426834

DM 357 DM 357 HS-TR

Swath discs for operation without conditioner



* 2x necessary

FEL429891

DM 306 FP DM 306 FZ

DM 8312 TL* DM 9314 TL* DM 306 TR





Stone guard

* 2x necessary

FEL429890

DM 306 FP-RC DM 306 FZ-RC

DM 8312 TL-RC* DM 306 TR-RC



Mower disc with conveyor wings

FEL429871

DM cutterbar

(compact angular gear)

not for:

DM 254 FK

DM 254 FP

DM 254 FP-S



Front mirror with holder



FEL429892

DM 306 FP-K

DM 306 FP

DM 306 FP-SL

DM 306 FP-KC

DM 306 FP-RC

DM 306 FZ DM 306 FZ-KC

DM 306 FZ-RC



Disc mowers

DM Accessories



Swath disc right

- 3,00 metre working width --> swath width approx.: 2,00 m
- 3,50 metre working width --> swath width approx.: 2,60 m
 4,00 metre working width --> swath width approx.: 3,00 m
- 4,50 metre working width --> swath width approx.: 3,50 m

FEL42799609

DM 306 TL DM 357 TL DM 408 TL DM 459 TL



Retrofit kit driveGUARD for one mower disc

Retrofit kit consisting of:

- Flange unit
- 2x driveGUARD-elements
- Washers
- Bolts

FEL428305

DM 204 FK DM 204 FK-S DM 204 DM 255 DM 306 DM 357



Hydraulic foldable protective covers

FEL429919

DM 306 FP DM 306 FP-SL DM 306 FP-KC DM 306 FP-RC





Set of running wheels 380/55-17

FEL42988601

DM 357 HS-TR-KC DM 357 HS-TR-RC



Metal plate

• Installation between cutter bar and conveyor belt

FEL429932

DM 9314 EL-TL-KCB

FEL429933

DM 8312 EL-TL-KCB



Curved blade

- For stony conditionsNOT FOR mowers with quick blade change

FEL138867

DM cutterbar (compact angular gear)



Tedders

TD Accessories



Night swath gear

Reduction of the rotor revs with same direction of rotation of the spinner for the depositing of small swaths instead of spreading the forage and less dew penetrating the forage overnight

FEL48464609

TD 454 DN

TD 524 DN

TD 676 DN

TD 776 DN

TD 776 TRC

TD 868 TRC

FEL15362409

TD 1008 TRC

TD 1310 TRC

TD 1008 TR-HYDRO

TD 1310 TR-HYDRO

FEL48465009

TD 868 DN



Electric lighting

FEL152500

TD 404 DSR

TD 404 DN

TD 434 DN

TD 576 DN





Electric lighting

FEL15360709

TD 454 DN TD 524 DN TD 676 DN TD 776 DN TD 868 DN



Electric lighting

To be mounted on warning plates 715 735 0000 / FEL150434 only

FEL15043309

TD 1008 TR-HYDRO TD 1310 TR-HYDRO



CH reflector set

FEL150732

TD alpin-serie
TD rear 3-point linkage



Tedders

TD Accessories



1 set of locking axles (2x)

2 rotor axles can be locked e.g. when using the machine on slopes

· Less drifting of the machine down the slope

FEL48946709

TD 1008 TR-HYDRO



Contact wheel (15/6.00-6)

- Optionally available spring-centred creeper wheel (upper link is in a hanging mounting link on the 3-point hitch)
- · Contact wheel always sets down on ground in direction of travel
- Tractor 3-point hydraulics can be driven in floating position
- Contact wheel takes over the guiding of the machine over the contours of the ground
- Tedder is guided independently of the tractor



TD 454 DN

TD 524 DN

TD 676 DN

TD 776 DN



Contact wheel (13/6.50-6)

- Optionally available spring-centred creeper wheel
- · Contact wheel always sets down on ground in direction of travel
- Tractor 3-point hydraulics can be driven in floating position
- Contact wheel takes over the guiding of the machine over the contours of the ground
- Tedder is guided independently of the tractor
- Very small space between contact wheel and tines, i.e. optimal adjustment of the machine to the ground, even in the case of short-wave ground contours



TD 404 DN

TD 434 DN

TD 576 DN





Attachment kit

- Required for installing the tedder on standard tractors
- Displacement of 115 mm to the rear

FEL489731

TD 404 DN

TD 434 DN

TD 576 DN



Contact wheel (16/6.50-8)

- Optionally available spring-centred creeper wheel (upper link is in a hanging mounting link on the 3-point hitch)
- · Contact wheel always sets down on ground in direction of travel
- Tractor 3-point hydraulics can be driven in floating position
- · Contact wheel takes over the guiding of the machine over the contours of the ground
- Tedder is guided independently of the tractor





TD 868 DN



1 set of contact wheels (18.5/8.50-8)

- Tractor 3-point hydraulics can be driven in floating position
- Contact wheel takes over the guiding of the machine over the contours of the ground
- Tedder is guided independently of the tractor
- Very small space between contact wheel and tines, i.e. optimal adjustment of the machine to the ground, even in the case of short-wave ground contours

FEL48467601

TD 868 TRC



Tedders

TD Accessories



Warning plates set with reflectors

FEL150434

TD 1008 TR-HYDRO TD 1310 TR-HYDRO



Hydraulic edge spreading device

Additional 1x SAV necessary

Tilting of the machine using single-acting hydraulic cylinder

- Forage is not thrown onto adjacent areas
- Prevents the machine from drifting down extreme slopes

FEL48467509

TD 454 DN

TD 524 DN

TD 676 DN

TD 776 DN

TD 868 DN



Tine-loss safety guard (1x)

Maximum protection for following harvesting machines, in order to prevent damage from lost, broken-off tines

FEL152584

TD 404 DSR

TD 404 DN

TD 434 DN

TD 576 DN





Set of running wheels 340/55-16

FEL48467801

TD 1008 TRC TD 1310 TRC



Spare wheel with support (16/6.50-8 10 PR)

FEL49957101

TD 454 DN

TD 524 DN

TD 676 DN

TD 776 DN

TD 868 DN

TD 776 TRC

TD 868 TRC

TD 1008 TR-HYDRO

TD 1310 TR-HYDRO



Rakes

RK Accessories



Set of running wheels 380/55-17

FEL42988601

RK 842 SD-TRC



Contact wheel (15/6.00-6)

- Optionally available spring-centred creeper wheel (upper link is in a hanging mounting link on the 3 point hitch)
- Contact wheel always sets down on ground in direction of travel
- Tractor 3-point hydraulics can be driven in floating position
- Contact wheel takes over the guiding of the machine over the contours of the ground
- Tedder is guided independently of the tractor



RK 341 DSR RK 361 DSR RK 341 DN RK 361 DN RK 381 DN RK 391 DN

RK 421 DN RK 451 DN





Universal gear

Made of aluminium alloy casting for the front insert of the machine, suitable for front power take-off

- 540 rev/min anti-clockwise
- 1000 rev/min anti-clockwise and clockwise
- Not necessary with front power take-off 540 rev/min clockwise

FEL499563

RK 341 DSR RK 361 DSR



Front mounting kit

Front installation for

- Better overview of the machine
- Maximum protection of the forage, because mowings no longer driven over by the tractor
- Consisting of: contact wheel, relieving spring an all-round protection



FEL49956401

RK 341 DSR RK 361 DSR



Rakes

RK Accessories



1 Set of tandem axle with wheel (16/6.50-8)

Tandem axle ensures

- Best adjustment to the ground even on uneven ground
- Quiet running even at high driving speeds
- * 2 sets necessary



FEL49956501

RK 361 DN

RK 381 DN

RK 391 DN

RK 421 DN

RK 772 SD-TRC

RK 762 TRC

RK 802 TRC

RK 1254 TRC

FEL49956601

RK 662 SD-TRC

RK 672 SD-TRC

RK 662 TRC



Individual lifting for the rotors

One-sided lifting of the rotors

- Each can be lifted out separately using a SAV control unit
- In total 2 SAV control units are necessary on the tractor
- Possible to cleanly swath inaccessible places such as field edges and corners

FEL499567

RK 662 TRC

RK 762 TRC

RK 802 TRC

RK 802 TRC-PRO





Warning plates

FEL161555

RK 341 DSR RK 361 DSR RK 341 DN RK 361 DN RK 381 DN RK 391 DN RK 421 DN RK 451 DN RK 451 TR



Electric lighting

FEL161556

RK 341 DSR
RK 361 DSR
RK 341 DN
RK 361 DN
RK 381 DN
RK 391 DN
RK 421 DN
RK 451 DN
RK 451 TR



Rakes

RK Accessories



Additional swath former

- Enables the formation of 2 individual swaths
- To be recommended with large quantities of forage



FEL49956801

RK 662 SD-TRC

RK 672 SD-TRC

RK 772 SD-TRC

RK 842 SD-TRC

RK 842 SD-TRC-PRO



Hydraulic operation for the rear swath former

- Shorter equipping times when converting from transport to work position
- More effectiveness and area performance per hour

FEL49956909

RK 702 TR-SDX





Contact wheel (18/8.50-8)

- Optionally available spring-centred creeper wheel (upper link is in a hanging mounting link on the 3 point hitch)
- Contact wheel always sets down on ground in direction of travel
- Tractor 3-point hydraulics can be driven in floating position
- Contact wheel takes over the guiding of the machine over the contours of the ground
- Tedder is guided independently of the tractor





RK 702 TR-SDX



Fitting on a 1-rotor rake

Spare wheel with support (16/6.50-8 10 PR)



Fitting on a 2-rotor rake

FEL49957101

RK 361 DN

RK 381 DN

RK 391 DN

RK 421 DN

RK 451 DN

RK 451 TR

RK 662 SD-TRC

RK 672 SD-TRC

RK 772 SD-TRC

RK 842 SD-TRC

RK 842 SD-TRC-PRO

RK 662 TRC

RK 762 TRC

RK 802 TRC

RK 1254 TRC-EC

RK 1254 TRC

RK 1254 TRC-PRO

RK 1404 TRC-PRO



Rakes


RK Accessories



Electrohydraulic individual lift (preselect switching)

FEL49957801

RK 1404 TRC-PRO



5th tine conversion kit

• Only for the rear rotor

FEL499577

RK 1254 TRC RK 1254 TRC-PRO



Electrohydraulic individual lift (preselect switching)

- Single lift of the rotors conveniently possible from the tractor cat
- Preselect switching using toggle switch
- No further control unit required
- Power supply with 2-pin Cobo plug



FEL167861

RK 662 TRC RK 762 TRC RK 802 TRC RK 802 TRC-PRO





CH signage kit

FEL16954409

RK 662 SD-TRC
RK 672 SD-TRC
RK 772 SD-TRC
RK 842 SD-TRC
RK 842 SD-TRC-PRO
RK 662 TRC
RK 762 TRC
RK 802 TRC
RK 802 TRC
RK 1002 TRC-PRO
RK 1002 TRC-PRO
RK 1254 TRC-EC
RK 1254 TRC
RK 1254 TRC
RK 1254 TRC
RK 1254 TRC



Hydraulic set swath former

- Retrofitting not possible before model year 2018
- For rear use only

FEL499591

RK 341 DSR RK 361 DSR RK 341 DN RK 361 DN RK 381 DN RK 391 DN RK 421 DN RK 451 DN



www.agcopartsandservice.com